

Web Images Maps News Shopping Gmail more ▾

Sign in

Google

cache probe trace predicate

Search

Advanced Search  
Preferences

Web

Results 1 - 10 of about 18,300 for **cache probe trace predicate**. (0.30 seconds)

### Mac OS X Manual Page For dtrace(1)

-i Specify **probe** identifier to **trace** or list (-l option). ... -p Grab the specified process-ID pid, **cache** its symbol tables, and exit upon its completion. ...  
developer.apple.com/documentation/Darwin/Reference/ManPages/man1/dtrace.1.html - 27k  
- Cached - [Similar pages](#)

### prstat(1M): DTrace Solaris vs. OS X: version & dtrace(1M)

[-i **probe-id** [[ **predicate** ] action ]] [ args ... ] **predicate** -> '/' D-expression '/' ... -p grab specified process-ID and **cache** its symbol tables ...  
prstat.blogspot.com/2008/02/dtrace-solaris-vs-mac-version-dtrace1m.html - 85k -  
Cached - [Similar pages](#)

### DTrace Introduction

The action(s) specified are to be run if the **probe** fires and the **predicate** is true. Each recording action dumps data to a **trace** buffer. ...  
www.princeton.edu/~unix/Solaris/troubleshoot/dtrace.html - 30k - Cached - [Similar pages](#)

### 14. dtrace(1M) Utility (Solaris Dynamic Tracing Guide)

where **predicate** is any D **predicate** enclosed in slashes // and action is any D statement list .... Specify **probe** identifier to **trace** or list (-l option). ...  
docs.sun.com/app/docs/doc/817-6223/chp-dtrace1m?a=view - 35k - Cached - [Similar pages](#)

### UNIX man pages : dtrace (7)

-i **probe-id**[[**predicate**] action] Specify **probe** identifier (**probe-id**) to **trace** or list (-l option). You can specify **probe** IDs using decimal integers as shown ...  
compute.cnr.berkeley.edu/cgi-bin/man-cgi?dtrace+7 - 25k - Cached - [Similar pages](#)

### [PDF] Form-Based Proxy Caching for Database-Backed Web Sites

File Format: PDF/Adobe Acrobat - [View as HTML](#)  
a top-N, applying the top-N **predicate** at the proxy before. returning results to the user. ... our **cache** merges this result with the result of the **probe** ...  
www.cs.wisc.edu/niagara/papers/formProxyVLDB.pdf - [Similar pages](#)

### jdtrace Example at OpenSolaris.org

-b set **trace** buffer size -c run specified command and exit upon its completion ... **probe** name  
-o set output file -p grab specified process-ID and **cache** its ...  
opensolaris.org/os/project/dtrace-chime/java\_dtrace\_api/  
jdtrace/?jsessionid=2F186D186A88DAE5D18F5F3A60D532B6 - 18k -  
Cached - [Similar pages](#)

### Byte Addressable Little endian Big endian ISA Microarchitecture ...

Priority **Trace** bit Compatability bit 1's catching property SRAM vs. ... Slot Branch Prediction  
Squashing **Predicate** Predicated Execution **Predicate** Registers ...  
users.ece.utexas.edu/~patt/04f.360N/handouts/buzzwords-final.txt - 8k -  
Cached - [Similar pages](#)

### DTrace Topics Cheatsheets Checklists - Siwiki

It has historically required a special "TRACE" build.) The format string specified with the VTRACE **probe** is ignored. VTRACE is only available in DEBUG ...  
www.solarisinternals.com/wiki/index.php/DTrace\_Topics\_Cheatsheets\_Checklists - 54k -